

ORDER YOUR **KAWHE/COFFEE** IN MĀORI

He mōwai māku I'll have a flat white
He pango poto māku I'll have a short black
He pango roa māku I'll have a long black
He rate pīni māku I'll have a soy latte
He kaputino māku I'll have a cappuccino
He rate māku I'll have a latte
He tiakarete wera māku I'll have a hot chocolate

Rahi Size



(S) **Paku**



(M) **Waenga**



(L) **Nui**

Kei te pēhea koe?
How's it going?

Anei taku kapu mau tonu
Here is my reusable cup

Hei kawē atu
To take away

Ki konei
To have here

McCafé

1. What's the Māori word for...

(a) "long"?

(b) "hot"?

2. How would you order a large cappuccino?

3. What's the word for chocolate?

AthNLP 2025

Machine Translation and Multilinguality

Antonis Anastasopoulos



***Acknowledgement: Many slides are taken from
Greg Durrett CS388@UT Austin,
Graham Neubig's Advanced NLP course@CMU
and Philipp Koehn's MT course@JHU***

Machine Translation

Machine Translation

- Intro

Machine Translation

- Intro
- A historical note

Machine Translation

- Intro
- A historical note
 - Alignment and EM algorithm

Machine Translation

- Intro
- A historical note
 - Alignment and EM algorithm
- MT Evaluation

Machine Translation

- Intro
- A historical note
 - Alignment and EM algorithm
- MT Evaluation
- Neural MT and LLM-based MT

Machine Translation

- Intro
- A historical note
 - Alignment and EM algorithm
- MT Evaluation
- Neural MT and LLM-based MT
- Semi-supervised and Unsupervised MT

Machine translation

Machine translation

- Machine Translation (MT) is the task of translating a sentence x from one language (the source language) to a sentence y in another language (the target language).

Machine translation

- Machine Translation (MT) is the task of translating a sentence x from one language (the source language) to a sentence y in another language (the target language).

Machine translation

- Machine Translation (MT) is the task of translating a sentence x from one language (the source language) to a sentence y in another language (the target language).

x : *L'homme est né libre, et partout il est dans les fers*

Machine translation

- Machine Translation (MT) is the task of translating a sentence x from one language (the source language) to a sentence y in another language (the target language).

x : *L'homme est né libre, et partout il est dans les fers*

Machine translation

- Machine Translation (MT) is the task of translating a sentence x from one language (the source language) to a sentence y in another language (the target language).

x : *L'homme est né libre, et partout il est dans les fers*

y : Man is born free, but everywhere he is in chains

Machine translation

- Machine Translation (MT) is the task of translating a sentence x from one language (the source language) to a sentence y in another language (the target language).

x : *L'homme est né libre, et partout il est dans les fers*



y : Man is born free, but everywhere he is in chains

Machine Translation



Machine Translation

- The classic test of language understanding!



Machine Translation

- The classic test of language understanding!
 - Both language analysis & generation



Machine Translation

- The classic test of language understanding!
 - Both language analysis & generation
- Big MT needs ... for humanity ... and commerce



Machine Translation

- The classic test of language understanding!
 - Both language analysis & generation
- Big MT needs ... for humanity ... and commerce
 - Translation is a US\$40 billion a year industry



Machine Translation

- The classic test of language understanding
 - Both language analysis & generation
- Big MT needs ... for humanity ... and commerce
 - Translation is a US\$40 billion a year industry
 - Huge in Europe, growing in Asia






Machine Translation

- The classic test of language understanding!
 - Both language analysis & generation
- Big MT needs ... for humanity ... and commerce
 - Translation is a US\$40 billion a year industry
 - Huge in Europe, growing in Asia
 - Large social/government/military as well as commercial needs









CLASSIC SOUPS

				Sm.	Lg.
清 燉 雞 湯	57.	House Chicken Soup (Chicken, Celery, Potato, Onion, Carrot)	1.50	2.75	
雞 飯 湯	58.	Chicken Rice Soup	1.85	3.25	
雞 麵 湯	59.	Chicken Noodle Soup	1.85	3.25	
廣 東 雲 吞	60.	Cantonese Wonton Soup.....	1.50	2.75	
蕃 茄 蛋 湯	61.	Tomato Clear Egg Drop Soup	1.65	2.95	
雲 吞 湯	62.	Regular Wonton Soup	1.10	2.10	
酸 辣 湯	63. 24	Hot & Sour Soup	1.10	2.10	
蛋 花 湯	64.	Egg Drop Soup.....	1.10	2.10	
雲 吞 湯	65.	Egg Drop Wonton Mix.....	1.10	2.10	
豆 腐 菜 湯	66.	Tofu Vegetable Soup	NA	3.50	
雞 玉 米 湯	67.	Chicken Corn Cream Soup	NA	3.50	
蟹 肉 玉 米 湯	68.	Crab Meat Corn Cream Soup.....	NA	3.50	
海 鮮 湯	69.	Seafood Soup.....	NA	3.50	

The need for Machine Translation

The need for Machine Translation

- Huge commercial use

The need for Machine Translation

- Huge commercial use
 - Google translates over 100 billion words a day

The need for Machine Translation

- Huge commercial use
 - Google translates over 100 billion words a day
 - Facebook in 2016 rolled out new homegrown MT

The need for Machine Translation

- Huge commercial use
 - Google translates over 100 billion words a day
 - Facebook in 2016 rolled out new homegrown MT
 - eBay uses MT to enable cross-border trade

The need for Machine Translation

- Huge commercial use
 - Google translates over 100 billion words a day
 - Facebook in 2016 rolled out new homegrown MT
 - eBay uses MT to enable cross-border trade
- NMT is the flagship task for NLP Deep Learning

The need for Machine Translation

- Huge commercial use
 - Google translates over 100 billion words a day
 - Facebook in 2016 rolled out new homegrown MT
 - eBay uses MT to enable cross-border trade
- NMT is the flagship task for NLP Deep Learning
 - RNNs? Encoder-decoder? Attention mechanism?

The need for Machine Translation

- Huge commercial use
 - Google translates over 100 billion words a day
 - Facebook in 2016 rolled out new homegrown MT
 - eBay uses MT to enable cross-border trade
- NMT is the flagship task for NLP Deep Learning
 - RNNs? Encoder-decoder? Attention mechanism?
- NMT research has pioneered many of the recent innovations of NLP Deep Learning

A historical note

1950s: Early Machine Translation




Fig. 7: Flowchart of part of the dictionary lookup procedures (from Sheridan 1955)

Flow chart of the dictionary look-up procedures ([source](#))

1950s: Early Machine Translation

- Machine Translation research began in the early 1950s.




Fig. 7: Flowchart of part of the dictionary lookup procedures (from Sheridan 1955)

Flow chart of the dictionary look-up procedures (source)

1950s: Early Machine Translation

- Machine Translation research began in the early 1950s.
- Mostly Russian → English (motivated by the Cold War)




Fig. 7: Flowchart of part of the dictionary lookup procedures (from Sheridan 1955)

Flow chart of the dictionary look-up procedures ([source](#))

1950s: Early Machine Translation

- Machine Translation research began in the early 1950s.
- Mostly Russian → English (motivated by the Cold War)
 - Georgetown–IBM experiment (1954)




Fig. 7: Flowchart of part of the dictionary lookup procedures (from Sheridan 1955)

Flow chart of the dictionary look-up procedures ([source](#))

1950s: Early Machine Translation

- Machine Translation research began in the early 1950s.
- Mostly Russian → English (motivated by the Cold War)
 - Georgetown–IBM experiment (1954)
- Systems were mostly rule-based, using a bilingual dictionary to map Russian words to their English counterparts




Fig. 7: Flowchart of part of the dictionary lookup procedures (from Sheridan 1955)

Flow chart of the dictionary look-up procedures ([source](#))

1990s-2010s: Statistical Machine Translation

1990s-2010s: Statistical Machine Translation

- Core idea: Learn a probabilistic model from data


1990s-2010s: Statistical Machine Translation

- Core idea: Learn a probabilistic model from data
- Suppose we're translating French $\rightarrow$ English.


1990s-2010s: Statistical Machine Translation

- Core idea: Learn a probabilistic model from data
- Suppose we're translating French $\rightarrow$ English.
- We want to find best English sentence y , given French sentence x

Egyptian



Greek



One naturally wonders if the problem of translation could conceivably be treated as a problem in cryptography. When I look at an article in Russian, I say: *‘This is really written in English, but it has been coded in some strange symbols. I will now proceed to decode.’*



Warren Weaver to Norbert Wiener, March, 1947

Noisy Channel MT

We want a model of $p(e|f)$



Noisy Channel MT

We want a model of $p(e|f)$

Confusing foreign sentence



Noisy Channel MT


We want a model of $p(\mathbf{e}|\mathbf{f})$

Confusing foreign sentence

Possible English translation



Noisy Channel MT



Noisy Channel MT

$$\hat{e} = \arg \max_e p(e|f)$$

$$= \arg \max_e \frac{p(e) \times p(f|e)}{p(f)}$$

$$= \arg \max_e \boxed{p(e)} \times \boxed{p(f|e)}$$

“Language Model”

“Translation Model”

Noisy Channel Division of Labor

- Language model – $p(\mathbf{e})$
 - is the translation fluent, grammatical, and idiomatic?
 - use any model of $p(\mathbf{e})$ – typically an n -gram model
- Translation model – $p(\mathbf{f}|\mathbf{e})$
 - translation probability
 - ensures adequacy of translation

Translation Model

- $p(\mathbf{f}|\mathbf{e})$ gives the channel probability – the probability of translating an English sentence into a foreign sentence
- $\mathbf{f}$ = je voudrais un peu de frommage $p(\mathbf{f}|\mathbf{e})$
- $\mathbf{e}_1$ = I would like some cheese 0.4
- $\mathbf{e}_2$ = I would like a little of cheese 0.5
- $\mathbf{e}_3$ = There is no train to Barcelona >0.00001

Translation Model

- How do we parameterize $p(\mathbf{f}|\mathbf{e})$?

$$p(\mathbf{f}|\mathbf{e}) = \frac{\text{count}(\mathbf{f}, \mathbf{e})}{\text{count}(\mathbf{e})} \quad ?$$

- There are a lot of sentences: this won't generalize to new inputs

Lexical Translation

Lexical Translation

- How do we translate a word? Look it up in a dictionary!

Lexical Translation

- How do we translate a word? Look it up in a dictionary!

Haus: house, home, shell, household

Lexical Translation

- How do we translate a word? Look it up in a dictionary!

Haus: house, home, shell, household

- Multiple translations

Lexical Translation

- How do we translate a word? Look it up in a dictionary!

Haus: house, home, shell, household

- Multiple translations
 - Different word senses, different registers, different inflections

Lexical Translation

- How do we translate a word? Look it up in a dictionary!

Haus: house, home, shell, household

- Multiple translations
 - Different word senses, different registers, different inflections
 - *house, home* are common

Lexical Translation

- How do we translate a word? Look it up in a dictionary!

Haus: house, home, shell, household

- Multiple translations
 - Different word senses, different registers, different inflections
 - *house, home* are common
 - *shell* is specialized (the Haus of a snail is its shell)

How common is each?

Translation	Count
house	5000
home	2000
shell	100
household	80

MLE


$$\hat{p}_{\text{MLE}}(e \mid \text{Haus}) = \begin{cases} 0.696 & \text{if } e = \text{house} \\ 0.279 & \text{if } e = \text{home} \\ 0.014 & \text{if } e = \text{shell} \\ 0.011 & \text{if } e = \text{household} \\ 0 & \text{otherwise} \end{cases}$$

Lexical Translation

- Goal: a model $p(\mathbf{e}|\mathbf{f},m)$
- where $\mathbf{e}$ and $\mathbf{f}$ are complete English and Foreign sentences


Lexical Translation

- Goal: a model $p(\mathbf{e}|\mathbf{f},m)$
- where $\mathbf{e}$ and $\mathbf{f}$ are complete English and Foreign sentences


$$\mathbf{e} = \langle e_1, e_2, \dots, e_m \rangle$$

Lexical Translation

- Goal: a model $p(\mathbf{e}|\mathbf{f},m)$
- where $\mathbf{e}$ and $\mathbf{f}$ are complete English and Foreign sentences

$$\mathbf{e} = \langle e_1, e_2, \dots, e_m \rangle \quad \mathbf{f} = \langle f_1, f_2, \dots, f_n \rangle$$
A diagram consisting of two blue arrows. One arrow originates from the vector $\mathbf{e}$ in the equation below and points to the $\mathbf{e}$ in the model $p(\mathbf{e}|\mathbf{f},m)$ in the list above. The other arrow originates from the vector $\mathbf{f}$ in the equation below and points to the $\mathbf{f}$ in the same model.

Lexical Translation

Lexical Translation

- Goal: a model $p(\mathbf{e}|\mathbf{f},m)$

Lexical Translation

- Goal: a model $p(\mathbf{e}|\mathbf{f},m)$
- where $\mathbf{e}$ and $\mathbf{f}$ are complete English and Foreign sentences

Lexical Translation

- Goal: a model $p(\mathbf{e}|\mathbf{f},m)$
- where $\mathbf{e}$ and $\mathbf{f}$ are complete English and Foreign sentences
- Lexical translation makes the following ***assumptions***:

Lexical Translation

- Goal: a model $p(\mathbf{e}|\mathbf{f},m)$
- where $\mathbf{e}$ and $\mathbf{f}$ are complete English and Foreign sentences
- Lexical translation makes the following ***assumptions***:
 - Each word $\mathbf{e}_i$ in $\mathbf{e}$ is generated from exactly one word in $\mathbf{f}$

Lexical Translation

- Goal: a model $p(\mathbf{e}|\mathbf{f},m)$
- where $\mathbf{e}$ and $\mathbf{f}$ are complete English and Foreign sentences
- Lexical translation makes the following ***assumptions***:
 - Each word $\mathbf{e}_i$ in $\mathbf{e}$ is generated from exactly one word in $\mathbf{f}$
 - Thus, we have a latent *alignment* $\mathbf{a}_i$ that indicates which word $\mathbf{e}_i$ “came from.” Specifically it came from $\mathbf{f}_{\mathbf{a}_i}$.

Lexical Translation

- Goal: a model $p(\mathbf{e}|\mathbf{f},m)$
- where $\mathbf{e}$ and $\mathbf{f}$ are complete English and Foreign sentences
- Lexical translation makes the following ***assumptions***:
 - Each word $\mathbf{e}_i$ in $\mathbf{e}$ is generated from exactly one word in $\mathbf{f}$
 - Thus, we have a latent *alignment* $\mathbf{a}_i$ that indicates which word $\mathbf{e}_i$ “came from.” Specifically it came from $\mathbf{f}_{\mathbf{a}_i}$.
 - Given the alignments $\mathbf{a}$, translation decisions are conditionally independent of each other and depend *only* on the aligned source word $\mathbf{f}_{\mathbf{a}_i}$.


Lexical Translation

- Putting our assumptions together, we have:

$$p(\mathbf{e} \mid \mathbf{f}, m) = \underbrace{\sum_{\mathbf{a} \in [0, n]^m} p(\mathbf{a} \mid \mathbf{f}, m)}_{p(\text{Alignment})} \times \underbrace{\prod_{i=1}^m p(e_i \mid f_{a_i})}_{p(\text{Translation} \mid \text{Alignment})}$$

What is alignment?

- Alignment is the correspondence between particular words in the translated sentence pair.




Alignment

$$p(\mathbf{a} \mid \mathbf{f}, m)$$

- Most of the action for the first 10 years of MT was here. Words weren't the problem. Word *order* was hard.

Alignment


- Alignments can be visualized by drawing links between two sentences, and they are represented as vectors of positions:



$$\mathbf{a} = (1, 2, 3, 4)^{\top}$$

Reordering


- Words may be reordered during translation



$$\mathbf{a} = (3, 4, 2, 1)^{\top}$$

Word Dropping


- A source word may not be translated at all



$$\mathbf{a} = (2, 3, 4)^{\top}$$

Word Insertion


- Words may be inserted during translation
- E.g. English **just** does not have an equivalent
- But these words must be explained – we typically assume every source sentence contains a NULL token



$$\mathbf{a} = (1, 2, 3, 0, 4)^{\top}$$

One-to-many Translation


- A source word may translate into **more than one** target word



$$\mathbf{a} = (1, 2, 3, 4, 4)^{\top}$$

Many-to-one Translation

- More than one source word may **not** translate as a unit in lexical translation



$\mathbf{a} = ???$

$\mathbf{a} = (1, 2, (3, 4)^\top)^\top \quad ?$

IBM Model 1

- Simplest possible lexical translation model
- Additional assumptions:
 - The m alignment decisions are independent
 - The alignment distribution for each a_i is uniform over all source words and NULL

for each $i \in [1, 2, \dots, m]$

$$a_i \sim \text{Uniform}(0, 1, 2, \dots, n)$$


$$e_i \sim \text{Categorical}(\boldsymbol{\theta}_{f_{a_i}})$$

Translating with Model 1

0	1	2	3	4
NULL	das	Haus	ist	klein


<u>1</u>	<u>2</u>	<u>3</u>	<u>4</u>
----------	----------	----------	----------

Translating with Model 1



Language model says: 😊

Translating with Model 1



Language model says: 😞

Learning Lexical Translation Models

Learning Lexical Translation Models

- How do we learn the parameters $p(e|f)$?

Learning Lexical Translation Models

- How do we learn the parameters $p(e|f)$?
- “Chicken and egg” problem

Learning Lexical Translation Models

- How do we learn the parameters $p(e|f)$?
- “Chicken and egg” problem
 - If we had the alignments, we could estimate the translation probabilities (MLE estimation)

Learning Lexical Translation Models

- How do we learn the parameters $p(e|f)$?
- “Chicken and egg” problem
 - If we had the alignments, we could estimate the translation probabilities (MLE estimation)
 - If we had the translation probabilities we could find the most likely alignments (greedy)

Learning Lexical Translation Models

- How do we learn the parameters $p(e|f)$?
- “Chicken and egg” problem
 - If we had the alignments, we could estimate the translation probabilities (MLE estimation)
 - If we had the translation probabilities we could find the most likely alignments (greedy)



Learning Lexical Translation Models

- How do we learn the parameters $p(e|f)$?
- “Chicken and egg” problem
 - If we had the alignments, we could estimate the translation probabilities (MLE estimation)
 - If we had the translation probabilities we could find the most likely alignments (greedy)



EM Algorithm

EM Algorithm

- Pick some random (or uniform) starting parameters

EM Algorithm

- Pick some random (or uniform) starting parameters
- Repeat until bored (~5 iterations for lexical translation models):

EM Algorithm

- Pick some random (or uniform) starting parameters
- Repeat until bored (~5 iterations for lexical translation models):
 - Using the current parameters, compute “expected” alignments $p(\mathbf{a}_i | \mathbf{e}, \mathbf{f})$ for every target word token in the training data

EM Algorithm

- Pick some random (or uniform) starting parameters
- Repeat until bored (~5 iterations for lexical translation models):
 - Using the current parameters, compute “expected” alignments $p(\mathbf{a}_i | \mathbf{e}, \mathbf{f})$ for every target word token in the training data
 - Keep track of the expected number of times f translates into e throughout the whole corpus

EM Algorithm




- Pick some random (or uniform) starting parameters
- Repeat until bored (~5 iterations for lexical translation models):
 - Using the current parameters, compute “expected” alignments $p(\mathbf{a}_i | \mathbf{e}, \mathbf{f})$ for every target word token in the training data
 - Keep track of the expected number of times f translates into e throughout the whole corpus
 - Keep track of the number of times f is used in the source of any translation

EM Algorithm

- Pick some random (or uniform) starting parameters
- Repeat until bored (~5 iterations for lexical translation models):
 - Using the current parameters, compute “expected” alignments $p(\mathbf{a}_i | \mathbf{e}, \mathbf{f})$ for every target word token in the training data
 - Keep track of the expected number of times f translates into e throughout the whole corpus
 - Keep track of the number of times f is used in the source of any translation
 - Use these estimates in the standard MLE equation to get a better set of parameters

EM for Model 1

... la maison ... la maison blue ... la fleur ...




... the house ... the blue house ... the flower ...

- Initial step: all alignments equally likely
- Model learns that, e.g., **la** is often aligned with **the**

EM for Model 1


... la maison ... la maison blue ... la fleur ...



... the house ... the blue house ... the flower ...


- After one iteration
- Alignments, e.g., between **la** and **the** are more likely

EM for Model 1



- After another iteration
- It becomes apparent that alignments, e.g., between **fleur** and **flower** are more likely (pigeon hole principle)

EM for Model 1



- Parameter estimation from the aligned corpus

Convergence

das Haus
the house

das Buch
the book

ein Buch
a book

<i>e</i>	<i>f</i>	initial	1st it.	2nd it.	3rd it.	...	final
the	das	0.25	0.5	0.6364	0.7479	...	1
book	das	0.25	0.25	0.1818	0.1208	...	0
house	das	0.25	0.25	0.1818	0.1313	...	0
the	buch	0.25	0.25	0.1818	0.1208	...	0
book	buch	0.25	0.5	0.6364	0.7479	...	1
a	buch	0.25	0.25	0.1818	0.1313	...	0
book	ein	0.25	0.5	0.4286	0.3466	...	0
a	ein	0.25	0.5	0.5714	0.6534	...	1
the	haus	0.25	0.5	0.4286	0.3466	...	0
house	haus	0.25	0.5	0.5714	0.6534	...	1

From words to
phrases

Word Alignment

	michael	geht	davon	aus	,	dass	er	im	haus	bleibt
michael										
assumes										
that										
he										
will										
stay										
in										
the										
house										

Extracting Phrase Pairs

	michael	geht	davon	aus	,	dass	er	im	haus	bleibt
michael										
assumes										
that										
he										
will										
stay										
in										
the										
house										

extract phrase pair consistent with word alignment:

assumes that / geht davon aus , dass

Phrase Pair Extraction

	michael	geht	davon	aus	,	dass	er	im	haus	bleibt
michael										
assumes										
that										
he										
will										
stay										
in										
the										
house										

Smallest phrase pairs:

michael — michael
assumes — geht davon aus / geht davon aus ,
that — dass / , dass
he — er
will stay — bleibt
in the — im
house — haus

unaligned words (here: German comma) lead to multiple translations

Larger Phrase Pairs

	michael	geht	davon	aus	,	dass	er	im	haus	bleibt
michael										
assumes										
that										
he										
will										
stay										
in										
the										
house										

michael assumes — michael geht davon aus / michael geht davon aus ,
 assumes that — geht davon aus , dass ; assumes that he — geht davon aus , dass er
 that he — dass er / , dass er ; in the house — im haus
 michael assumes that — michael geht davon aus , dass
 michael assumes that he — michael geht davon aus , dass er
 michael assumes that he will stay in the house — michael geht davon aus , dass er im haus bleibt
 assumes that he will stay in the house — geht davon aus , dass er im haus bleibt
 that he will stay in the house — dass er im haus bleibt ; dass er im haus bleibt ,
 he will stay in the house — er im haus bleibt ; will stay in the house — im haus bleibt

Extensions



- Phrase-based MT:
 - Allow multiple words to translate as chunks (including many-to-one)
 - Introduce another latent variable, the source *segmentation*

Maria	no	dio	una	bofetada	a	la	bruja	verde
Mary	not	give	a	slap	to	the	witch	green
	did not		a	slap	by		hag	bawdy
	no		slap		to the		green	witch
	did not give				the			
						the	witch	

Adapted from Koehn (2006)

Another Paradigm: Syntax-Based MT

- Syntactic structure
- Rules of the form:
- $X\text{之一} \rightarrow \text{one of the } X$



Chang (2005),
Galley et al. (2006)

2014

(dramatic reenactment)

2014

Neural Machine Translation

MT research

(dramatic reenactment)

What is Neural Machine Translation?

- Neural Machine Translation (NMT) is a way to do Machine Translation with a single neural network
- The neural network architecture is called sequence-to-sequence (aka seq2seq) and it involves two RNNs.

Conditional Language Models

$$P(Y|X) = \prod_{j=1}^J P(y_j \mid X, y_1, \dots, y_{j-1})$$

Conditional Language Models

$$P(Y|X) = \prod_{j=1}^J P(y_j \mid \overline{X}, y_1, \dots, y_{j-1})$$

Added Context!




Neural Machine Translation (NMT)

The sequence-to-sequence model

Encoding of the source sentence.
Provides initial hidden state
for Decoder RNN.


Encoder RNN



Source sentence (input)

Encoder RNN produces
an **encoding** of the
source sentence.

Target sentence (output)




Decoder RNN

Decoder RNN is a Language Model that generates
target sentence conditioned on **encoding**.

Note: This diagram shows **test time** behavior:
decoder output is fed in> as next step's input

Neural Machine Translation (NMT)



Seq2seq is optimized as a single system.
Backpropagation operates "end to end".

Advantages of NMT

Advantages of NMT

- Compared to SMT, NMT has many advantages:

Advantages of NMT

- Compared to SMT, NMT has many advantages:
- Better performance

Advantages of NMT

- Compared to SMT, NMT has many advantages:
- Better performance
 - More fluent

Advantages of NMT

- Compared to SMT, NMT has many advantages:
- Better performance
 - More fluent
 - Better use of context

Advantages of NMT

- Compared to SMT, NMT has many advantages:
- Better performance
 - More fluent
 - Better use of context
 - Better use of phrase similarities

Advantages of NMT

- Compared to SMT, NMT has many advantages:
- Better performance
 - More fluent
 - Better use of context
 - Better use of phrase similarities
- A single neural network to be optimized end-to-end

Advantages of NMT

- Compared to SMT, NMT has many advantages:
- Better performance
 - More fluent
 - Better use of context
 - Better use of phrase similarities
- A single neural network to be optimized end-to-end
 - No subcomponents to be individually optimized

Advantages of NMT

- Compared to SMT, NMT has many advantages:
- Better performance
 - More fluent
 - Better use of context
 - Better use of phrase similarities
- A single neural network to be optimized end-to-end
 - No subcomponents to be individually optimized
- Requires much less human engineering effort

Advantages of NMT

- Compared to SMT, NMT has many advantages:
- Better performance
 - More fluent
 - Better use of context
 - Better use of phrase similarities
- A single neural network to be optimized end-to-end
 - No subcomponents to be individually optimized
- Requires much less human engineering effort
 - No feature engineering

Advantages of NMT

- Compared to SMT, NMT has many advantages:
- Better performance
 - More fluent
 - Better use of context
 - Better use of phrase similarities
- A single neural network to be optimized end-to-end
 - No subcomponents to be individually optimized
- Requires much less human engineering effort
 - No feature engineering
 - Same method for all language pairs

Disadvantages of NMT?

Disadvantages of NMT?

Compared to SMT:

Disadvantages of NMT?

Compared to SMT:

- NMT is less interpretable

Disadvantages of NMT?

Compared to SMT:

- NMT is less interpretable
 - Hard to debug

Disadvantages of NMT?

Compared to SMT:

- NMT is less interpretable
 - Hard to debug
- NMT is difficult to control

Disadvantages of NMT?

Compared to SMT:

- NMT is less interpretable
 - Hard to debug
- NMT is difficult to control
 - For example, can't easily specify rules or guidelines for translation

Disadvantages of NMT?

Compared to SMT:

- NMT is less interpretable
 - Hard to debug
- NMT is difficult to control
 - For example, can't easily specify rules or guidelines for translation
 - Safety concerns!

Generation

Can we find the best (most likely) translation?

Generation through Sampling

No but we can approximate it!

Generating New Sentences

Generating New Sentences

- Generate sentences:

while didn't choose end-of-sentence symbol:

calculate probability of

$$P(x_t \mid x_1, \dots, x_{t-1})$$

Greedy Decoding

- Generate next word conditioned on the context (i.e., the previously generated words)
- “Greedy”: always pick the most probable next word
$$x_t = \operatorname{argmax}_{\hat{x}} P(\hat{x} | x_1, \dots, x_{t-1})$$

Greedy Decoding


- Generate next word conditioned on the context (i.e., the previously generated words)
- “Greedy”: always pick the most probable next word
$$x_t = \operatorname{argmax}_{\hat{x}} P(\hat{x} | x_1, \dots, x_{t-1})$$
- Problem:
 - The most probable next word does not always lead to the most probable sentence;
 - We should be able to generate a diverse set of sentences!

Beam Search

- Beam search: instead of picking one high-probability word, maintain several paths

Beam Search

- Beam search: instead of picking one high-probability word, maintain several paths



Beam Search



Beam Search



a	0.001
the	0.0002
I	0.12
vou	0.04
cat	0.0004
movie	0.01
this	0.02
...	

Beam Search


$k=2$



a	0.001
the	0.0002
I	0.12 ←
you	0.04 ←
cat	0.0004
movie	0.01
this	0.02
...	


Beam Search

$k=2$



Beam Search


$k=2$



Beam Search

k=2


Expand



Beam Search


k=2

Expand




a	0.001	
the	0.0002	
hate	0.5	←
this	0.001	
cat	0.003	
movie	0.07	
don't	0.3	←
...	...	

Beam Search




a	0.001	
the	0.0002	
hate	0.5	←
this	0.001	
cat	0.003	
movie	0.07	
don't	0.3	←
...	...	

Beam Search




an	0.0012
be	0.0002
hate	0.5 ←
these	0.001
dog	0.003
movie	0.07
like	0.3 ←
...	...

Beam Search




an	0.0012
be	0.0002
hate	0.5 ←
these	0.001
dog	0.003
movie	0.07
like	0.3 ←
...	...


Beam Search




Beam Search



Beam Search



Beam Search



2022




~~MT research~~


NLP

(dramatic reenactment)

Benchmarking LLMs for Translation




LLMs for Translation: Robustness



Did Translation Models Get More Robust Without Anyone Even Noticing?

Ben Peters* and André F. T. Martins*†‡◊

The Tower models



LLM-powered translation

Simulate a translation pipeline with noisy inputs.



User prompt

Fix all errors in the following sentence.

If the sentence does not contain any errors, just copy it.

Do not change the meaning of the sentence or insert stylistic changes.

Sentence: Ontme, a meu amiga foi ao supermrcado mas estava fechado. Queria comprsr legumes e fruta.

Corrected sentence:



TowerInstruct

Ontem, a minha amiga foi ao supermercado mas estava fechado. Queria comprar legumes e fruta.



User prompt

Now, **translate** the corrected sentence from Portuguese into English.

English:



TowerInstruct

Yesterday, my friend went to the supermarket but it was closed. She wanted to buy vegetables and fruit.

correct pronoun resolution

LLM-powered translation

Introduce terminology/glossary terms on the prompt for terminology-aware translation

Without terminology terms:



User prompt

*Translate the source text from Portuguese to English.
Portuguese: Eu vou de férias este verão para Itália.
English:*



TowerInstruct

I'm going on holiday this summer to Italy.

With terminology terms:



User prompt

*Consider the following translation rule:
férias -> vacation
Translate the source text from Portuguese to English following the provided translation rules.
Portuguese: Eu vou de férias este verão para Itália.
English:*



TowerInstruct

I'm going on vacation this summer to Italy.

LLM-powered translation

Translate into multiple languages on the same conversation



User prompt

Translate the following text from Portuguese into English.

Portuguese: Ontem, a minha amiga foi ao supermercado mas estava fechado. Queria comprar legumes e fruta.

English:



TowerInstruct

Yesterday, my friend went to the supermarket but it was closed. She wanted to buy vegetables and fruit.



User prompt

Can you now translate into Spanish?



TowerInstruct

Ayer mi amiga fue al supermercado, pero estaba cerrado. Quería comprar verduras y fruta.



User prompt

Now translate to Italian.



TowerInstruct

Ieri la mia amica è andata al supermercato, ma era chiuso. Voleva comprare verdure e frutta.

Evaluation

Machine Translation (reference based)

Mi piacerebbe un
cappuccino freddo.

MT Model

I like one cold cappuccino.

Machine Translation (reference based)

Mi piacerebbe un
cappuccino freddo.

MT Model

I like one cold cappuccino.

reference: *I would like a cold cappuccino.*

Machine Translation (reference based)

Mi piacerebbe un
cappuccino freddo.

MT Model

I like one cold cappuccino.

reference: *I would like a cold cappuccino.*

Compare the output with the reference!

How do we evaluate MT?

How do we evaluate MT?

BLEU (Bilingual Evaluation Understudy)

How do we evaluate MT?

BLEU (Bilingual Evaluation Understudy)

- BLEU compares the machine-written translation to one or several human-written translation(s), and computes a similarity score based on:

How do we evaluate MT?

BLEU (Bilingual Evaluation Understudy)

- BLEU compares the machine-written translation to one or several human-written translation(s), and computes a similarity score based on:
 - n-gram precision (usually up to 3 or 4-grams)

How do we evaluate MT?

BLEU (Bilingual Evaluation Understudy)

- BLEU compares the machine-written translation to one or several human-written translation(s), and computes a similarity score based on:
 - n-gram precision (usually up to 3 or 4-grams)
 - Penalty for too-short system translations

How do we evaluate MT?

BLEU (Bilingual Evaluation Understudy)

- BLEU compares the machine-written translation to one or several human-written translation(s), and computes a similarity score based on:
 - n-gram precision (usually up to 3 or 4-grams)
 - Penalty for too-short system translations
- BLEU is useful but imperfect

How do we evaluate MT?

BLEU (Bilingual Evaluation Understudy)

- BLEU compares the machine-written translation to one or several human-written translation(s), and computes a similarity score based on:
 - n-gram precision (usually up to 3 or 4-grams)
 - Penalty for too-short system translations
- BLEU is useful but imperfect
 - There are many valid ways to translate a sentence

How do we evaluate MT?

BLEU (Bilingual Evaluation Understudy)

- BLEU compares the machine-written translation to one or several human-written translation(s), and computes a similarity score based on:
 - n-gram precision (usually up to 3 or 4-grams)
 - Penalty for too-short system translations
- BLEU is useful but imperfect
 - There are many valid ways to translate a sentence
 - So a good translation can get a poor BLEU score because it has low n-gram overlap with the human translation 😞

Machine Translation: BLEU

reference: I would like a cold cappuccino

hypothesis: I like one cold cappuccino

Machine Translation: BLEU

reference: I would like a cold cappuccino

hypothesis: I like one cold cappuccino

Unigrams	4/5
----------	-----

Machine Translation: BLEU

reference: I would like a cold cappuccino

hypothesis: I like one cold cappuccino

Unigrams	4/5
Bigrams	1/4

Machine Translation: BLEU

reference: I would like a cold cappuccino

hypothesis: I like one cold cappuccino

Unigrams	4/5
Bigrams	1/4
3-grams	0/3

Machine Translation: BLEU

reference: I would like a cold cappuccino

hypothesis: I like one cold cappuccino

Unigrams	4/5
Bigrams	1/4
3-grams	0/3
4-grams	0/2

Machine Translation: BLEU

reference: I would like a cold cappuccino

hypothesis: I like one cold cappuccino

Unigrams	4/5
Bigrams	1/4
3-grams	0/3
4-grams	0/2

————→ **average**

Machine Translation: BLEU

reference: I would like a cold cappuccino

hypothesis: I like one cold cappuccino

Unigrams	4/5
Bigrams	1/4
3-grams	0/3
4-grams	0/2

————→ **average**

Can we cheat?

Machine Translation: BLEU

reference: I would like a cold cappuccino

hypothesis: I like like like like one cold cappuccino

Unigrams	7/8
Bigrams	1/7
3-grams	0/6
4-grams	0/5

Can we cheat?

Solution: Only count each word once.

Machine Translation: BLEU

reference: I would like a cold cappuccino

hypothesis: I would like

Unigrams	3/3
Bigrams	2/2
3-grams	1/1
4-grams	—

Can we cheat?

Solution: Brevity Penalty.

MT: Problems with BLEU

reference: I would like a cold cappuccino

hypothesis 1: *I would like one cold cappuccino*

These three hypotheses have the same BLEU score!

Solution: Use paraphrases, synonyms, etc (Meteor)

MT: Problems with BLEU

reference: I would like a cold cappuccino

hypothesis 1: *I would like one cold cappuccino*

hypothesis 2: *I would like a cold espresso*

These three hypotheses have the same BLEU score!

Solution: Use paraphrases, synonyms, etc (Meteor)

MT: Problems with BLEU

reference: I would like a cold cappuccino

hypothesis 1: *I would like one cold cappuccino*

hypothesis 2: *I would like a cold espresso*

hypothesis 3: *I would like a cold monk*

These three hypotheses have the same BLEU score!

Solution: Use paraphrases, synonyms, etc (Meteor)

MT: Problems with BLEU

source: *behaving as if you are among those whom we could not civilize*

reference: *uygarlatıramadıklarımızdanmı,ssınızcasına*

Languages with Rich Morphology: How do we even evaluate this?

Solution: Use subwords, character-Fscore — chrF

MT: Human Evaluation

It is almost always better to ask humans!
e.g. in MT, we ask translators

Way 1:

We show system outputs to the annotators, and they provide a score (e.g. 1-5 Likert scale, or 0-100 score)

Way 2:

We show **2** system outputs to the annotators, and they annotate which one of the two they think is better.

Evaluation of Evaluation Metrics




- Automatic metrics are low cost, tunable, consistent
 - But are they correct?
- Yes, if they correlate with human judgement

Evidence of Shortcomings of Automatic Metrics




Post-edited output vs. statistical systems (NIST 2005)



Evidence of Shortcomings of Automatic Metrics



Rule-based vs. statistical systems



WMT Metrics Shared Task

- Annual event to evaluate metrics
- Piggy-backs on the WMT General Translation Task
 - new test set every year
 - research systems and commercial systems
 - lately also large language models
 - human evaluation of automatic evaluations
- New metrics proposed
- Evaluation by correlation with human judgments

Metric		avg corr
XCOMET-Ensemble	1	0.825
XCOMET-QE-Ensemble*	2	0.808
MetricX-23	2	0.808
GEMBA-MQM*	2	0.802
MetricX-23-QE*	2	0.800
mbr-metricx-qe*	3	0.788
MaTESe	3	0.782
CometKiwi*	3	0.782
COMET	3	0.779
BLEURT-20	3	0.776
KG-BERTScore*	3	0.774
sescorX	3	0.772
cometoid22-wmt22*	4	0.772
docWMT22CometDA	4	0.768
docWMT22CometKiwiDA*	4	0.767
Calibri-COMET22	4	0.767
Calibri-COMET22-QE*	4	0.755
YiSi-1	4	0.754
MS-COMET-QE-22*	5	0.744
prismRef	5	0.744
mre-score-labse-regular	5	0.743
BERTscore	5	0.742
XLsim	6	0.719
f200spBLEU	7	0.704
MEE4	7	0.704
tokengram_F	7	0.703
embed_llama	7	0.701
BLEU	7	0.696
chrF	7	0.694
eBLEU	7	0.692
Random-sysname*	8	0.529
prismSrc*	9	0.455

(WMT 2023)

Trained Metrics: COMET



- Two decades of evaluation campaigns for machine translation metrics
→ a lot of human judgment data
- Goal: automatic metric that correlates with human judgment
- Make it a machine learning problem
 - input: machine translation, reference translation
 - output: human annotation score
- COMET: Trained neural model for evaluation

Reference-Free Evaluation



- We have data in the form

input, translation, human reference → human judgment

- We can also train a model on

input, translation → human judgment

- CometKiwi: trained evaluation model without references
- Also called **quality estimation** or **confidence estimation**

Semisupervised and Unsupervised Methods

On Using Monolingual Corpora in Neural Machine Translation (Gulcehre et al. 2015)


Parallel

English

French


Monolingual

On Using Monolingual Corpora in Neural Machine Translation (Gulcehre et al. 2015)




Monolingual

On Using Monolingual Corpora in Neural Machine Translation (Gulcehre et al. 2015)




On Using Monolingual Corpora in Neural Machine Translation (Gulcehre et al. 2015)



Combine the two!

Back-translation (Sennrich et al. 2016)

Parallel




Monolingual

Back-translation (Sennrich et al. 2016)




Monolingual


Back-translation (Sennrich et al. 2016)



Back-translation (Sennrich et al. 2016)





Back-translation (Sennrich et al. 2016)



Dual Learning (He et al. 2016)

Parallel




Monolingual

Dual Learning (He et al. 2016)

Assume MT_{ef} , MT_{fe} , LM_e , LM_f

Parallel




Monolingual

Dual Learning (He et al. 2016)

Assume MT_{ef} , MT_{fe} , LM_e , LM_f

Parallel




Monolingual

Dual Learning (He et al. 2016)

Assume MT_{ef} , MT_{fe} , LM_e , LM_f

Parallel




Monolingual



Dual Learning (He et al. 2016)

Assume MT_{ef} , MT_{fe} , LM_e , LM_f

Parallel




Monolingual



Dual Learning (He et al. 2016)

Assume MT_{ef} , MT_{fe} , LM_e , LM_f

Parallel



Game:

Translate sample with MT_{ef}


Monolingual



Dual Learning (He et al. 2016)

Assume MT_{ef} , MT_{fe} , LM_e , LM_f

Parallel



Game:

Translate sample with MT_{ef}

Get reward with LM_f


Monolingual



Dual Learning (He et al. 2016)

Assume MT_{ef} , MT_{fe} , LM_e , LM_f

Parallel



Game:

Translate sample with MT_{ef}

Get reward with LM_f

Monolingual




Translate sample with MT_{fe}

Dual Learning (He et al. 2016)

Assume MT_{ef} , MT_{fe} , LM_e , LM_f

Parallel



Game:

Translate sample with MT_{ef}

Get reward with LM_f

Monolingual



Translate sample with MT_{fe}

Get reward with LM_e

Semi-Supervised Learning for MT (Cheng et al. 2016)

Parallel

English

French

Monolingual

bushi yu shalong juxing le huitan $\mathbf{x}'$

decoder



$P(\mathbf{x}'|\mathbf{y}; \overleftarrow{\theta})$

Bush held a talk with Sharon $\mathbf{y}$

encoder




$P(\mathbf{y}|\mathbf{x}; \overrightarrow{\theta})$


bushi yu shalong juxing le huitan $\mathbf{x}$

Semi-Supervised Learning for MT (Cheng et al. 2016)

Parallel




Monolingual




Semi-Supervised Learning for MT (Cheng et al. 2016)

Round-trip translation for supervision

Parallel




Monolingual



Semi-Supervised Learning for MT (Cheng et al. 2016)


Round-trip translation for supervision

Parallel



Translate e to f' with MT_{ef}


Monolingual



Semi-Supervised Learning for MT (Cheng et al. 2016)

Round-trip translation for supervision



Parallel



Translate e to f' with MT_{ef}

Translate f' to e' with MT_{fe}


Monolingual



Semi-Supervised Learning for MT (Cheng et al. 2016)

Round-trip translation for supervision

Parallel





Translate e to f' with MT_{ef}

Translate f' to e' with MT_{fe}


Loss from e and e'

Monolingual



Another idea: use monolingual data
to pretrain model components

Parallel



Monolingual

Another idea: use monolingual data to pretrain model components

Use the monolingual data to train the encoder and the decoder.

Parallel

English

French

Monolingual



Another idea: use monolingual data to pretrain model components






Figure 1. The encoder-decoder framework for our proposed MASS. The token “-” represents the mask symbol $[M]$.

Another idea: use monolingual data to pretrain model components



(a) Masked language modeling in BERT ($k = 1$)



(b) Standard language modeling ($k = m$)

From "MASS: Masked Sequence to Sequence Pre-training for Language Generation", Song et al. 2019.

Another idea: use monolingual data to pretrain model components




Figure 3. The BLEU score comparisons between MASS and the baseline on low-resource NMT with different scales of paired data.

From "MASS: Masked Sequence to Sequence Pre-training for Language Generation", Song et al. 2019.

Unsupervised Translation

... at the core of it all:
decipherment

French

$$\arg \max_{\theta} \prod_f P_{\theta}(f)$$

... at the core of it all:
decipherment

French

$$\arg \max_{\theta} \prod_f P_{\theta}(f)$$

Weaver (1955): *This is really English, encrypted in some strange symbols*


... at the core of it all:
decipherment

French

$$\arg \max_{\theta} \prod_f P_{\theta}(f)$$

Weaver (1955): *This is really English, encrypted in some strange symbols*

English



French


$$\arg \max_{\theta} \prod_f \sum_e P(e) \cdot P_{\theta}(f|e)$$

Unsupervised MT

(Lample et al. and Artetxe et al. 2018)

Unsupervised MT

(Lample et al. and Artetxe et al. 2018)



English

The diagram consists of two rounded rectangular blocks. The top block is blue and contains the word 'English' in white text. The bottom block is red and contains the word 'French' in white text. The blocks are positioned diagonally, with the blue block at the top-left and the red block at the bottom-right.

French

Unsupervised MT

(Lample et al. and Artetxe et al. 2018)

1. Embeddings + Unsup. BLI



English



French

Unsupervised MT

(Lample et al. and Artetxe et al. 2018)

1. Embeddings + Unsup. BLI
2. BLI $\rightarrow$ Word Translations



English



French

Unsupervised MT

(Lample et al. and Artetxe et al. 2018)

1. Embeddings + Unsup. BLI
2. BLI $\rightarrow$ Word Translations



English




French

Unsupervised MT


(Lample et al. and Artetxe et al. 2018)

1. Embeddings + Unsup. BLI
2. BLI $\rightarrow$ Word Translations
3. Train MT_{fe} and MT_{ef} systems



Unsupervised MT


(Lample et al. and Artetxe et al. 2018)



1. Embeddings + Unsup. BLI
2. BLI $\rightarrow$ Word Translations
3. Train MT_{fe} and MT_{ef} systems
4. Meanwhile, use unsupervised objectives (denoising LM)

Unsupervised MT


(Lample et al. and Artetxe et al. 2018)



1. Embeddings + Unsup. BLI
2. BLI $\rightarrow$ Word Translations
3. Train MT_{fe} and MT_{ef} systems
4. Meanwhile, use unsupervised objectives (denoising LM)
5. Iterate

Unsupervised MT


(Lample et al. and Artetxe et al. 2018)



1. Embeddings + Unsup. BLI
2. BLI $\rightarrow$ Word Translations
3. Train MT_{fe} and MT_{ef} systems
4. Meanwhile, use unsupervised objectives (denoising LM)
5. Iterate

Unsupervised MT

(Lample et al. and Artetxe et al. 2018)



1. Embeddings + Unsup. BLI
2. BLI $\rightarrow$ Word Translations
3. Train MT_{fe} and MT_{ef} systems
4. Meanwhile, use unsupervised objectives (denoising LM)
5. Iterate

NMT: the biggest success
story of NLP Deep Learning

NMT: the biggest success
story of NLP Deep Learning

NMT: the biggest success story of NLP Deep Learning

Neural Machine Translation went from a fringe research activity in 2014 to the leading standard method in 2016

NMT: the biggest success story of NLP Deep Learning

Neural Machine Translation went from a fringe research activity in 2014 to the leading standard method in 2016

- 2014: First seq2seq paper published

NMT: the biggest success story of NLP Deep Learning

Neural Machine Translation went from a fringe research activity in 2014 to the leading standard method in 2016

- 2014: First seq2seq paper published
- 2016: Google Translate switches from SMT to NMT

NMT: the biggest success story of NLP Deep Learning

Neural Machine Translation went from a fringe research activity in 2014 to the leading standard method in 2016

- 2014: First seq2seq paper published
- 2016: Google Translate switches from SMT to NMT
- **This is amazing!**


NMT: the biggest success story of NLP Deep Learning

Neural Machine Translation went from a fringe research activity in 2014 to the leading standard method in 2016

- 2014: First seq2seq paper published
- 2016: Google Translate switches from SMT to NMT
- **This is amazing!**
- SMT systems, built by hundreds of engineers over many years, outperformed by NMT systems trained by a handful of engineers in a few months

So is Machine Translation solved?


- Nope!
- Using common sense is still hard



?

So is Machine Translation solved?

- Nope!
- NMT picks up biases in training data



Didn't specify gender

So is Machine Translation solved?

- Nope!
- Uninterpretable systems do strange things

